



Model	VTRAC 1455	VTRAC 1655	VTRAC 1855	VTRAC 2055
Motor				
Fabrikant	Deutz WPC	Deutz WPC	Deutz WPC	Deutz WPC
Model	WP6T140E22	WP6T160E200	WP6T180E200	WP6T200E200
Type	Turbo	Turbo-Intercooler	Turbo-Intercooler	Turbo-Intercooler
Max koppel(N·m)/(rpm)	665/1400-1600	800/1400-1600	830/1400-1600	860/1400-1600
Cil.inhoud(L)	6,75	6,75	6,75	6,75
Brandstoftank(L)	320	320	320	320
Nominaal vermogen (pK(kW)/rpm)	145(105)/2200	160(118)/2200	180(132,5)/2200	200(147)/2200
Brandstofverbruik(g/kWh)	228	230	230	230
Transmissie				
Koppeling	Elektrisch bediend, wet multi-disc	Elektrisch bediend, wet multi-disc	Elektrisch bediend, wet multi-disc	Elektrisch bediend, wet multi-disc
Aftakas snelheid(rpm)	540/540E/1000/1000E	540/540E/1000/1000E	540/540E/1000	540/540E/1000/1000E
Versnellingen	40+40	40+40	40+40	40+40
Schakelmethode	power shift	power shift	power shift	power shift
Rem systeem				
Remmen	hydraulisch bediend, wet multi-disc	hydraulisch bediend, wet multi-disc	hydraulisch bediend, wet multi-disc	hydraulisch bediend, wet multi-disc
Handrem	hendel bediend, multi frictie plaat	hendel bediend, multi frictie plaat	hendel bediend, multi frictie plaat	hendel bediend, multi frictie plaat
Hydraulisch Systeem				
Olie opbrengst(L/min)	65	65	65	80
aantal ventielen	3	3	3	3
Hefinrichting				
Categorie	3	3	3	3
Hefvermogen(kN)	25,6	28,4	31,8	35,28
Regeling	Bosch EHR	Bosch EHR	Bosch EHR	Bosch EHR
Afmetingen				
Lengte/breedte/hoogte, mm	5500×2320×3170	5750×2320×3210	5750×2320×3210	5750×2320×3210
Wielbasis(mm)	2880	2880	2880	2950
Leeg gewicht(kg)	6044	6300	6300	6500
Bodemvrijheid(mm)	315,5	400	400	400
Draaicirkel(mm)	7000	7000	7000	8500
Banden voor	420/85 R30	420/85 R30	480/70 R30	480/70 R30
Banden achter	460/85 R38	520/85 R38	580/70 R38	580/70 R38